CROSSWAY

CROSSWAY LE City & Line14.5 m – DIESEL EURO VI STEP E









		CROSSWAY LE
		DIESEL EURO VI STEP E
LENGTH		14,495 mm
WIDTH		2,550 mm
HEIGHT		3,205 / 3,120 mm
WHEELBASE		6,945 mm / 1,530 mm
FRONT / REAR OVERHANG		2,725 / 3,295 mm
FRONT / MIDDLE / ACCESS HEIGHT		320 / 330 mm
FRONT / MIDDLE DOOR WIDTH		800 (LE Line) - 1,200 mm (LE City) / 1,200 mm
TURNING RADIUS (CURB TO CURB)		10,070 mm
TURNING RADIUS (WALL TO WALL)		11,930 mm
APPROACH / DEPARTURE ANGLES		7° / 7°
MAX. TECHNICALLY PERMISSIBLE GVW*		24,000 kg
MAX. TECHNICALLY PERMISSIBLE AXLE LOADS [®]	FRONT / MIDDLE / REAR AXLE (LINE)	6,300 / 11,600 kg / 6,300
	FRONT / MIDDLE / REAR AXLE (CITY)	7,200 / 12,000 kg / 6,300

* Max allowed vehicle axles load and GVW is depending on local regulation in registration country

	CURSOR 9
POWER @ 2500 RPM	265 kW (360 hp) @ 2,200 rpm
MAX TORQUE	I,600 Nm @I,200 rpm
DISPLACEMENT	8.7 litres

6 cylinders in line, vertical longitudinal at the rear





LAYOUT^(*)



E	- SEFEFEF	7000	
E		BBB	

Layout LE City: 45 passenger seats

Layout LE City: 49 passenger seats





Layout LE Line: 57+4 passenger seats

CROSSWAY

CROSSWAY LE City & Line 14.5 m – DIESEL EURO VI STEP E

BODY AND EXTERIOR EQUIPMENT

- Anticorrosion cataphoretic treatment of the structure and of the body, finished with a polyurethane resin final coat.
- LE City: Front & Middle doors 1,200 mm 2 leaves, external opening
- Le Line: Front door 800 mm I leaf, external opening / middle door 1,200 mm 2 leaves, external opening
- · External rearview mirrors, electrical control

INTERIOR EQUIPEMENT

- · Self-adhesive anti-slip PVC carpet on the floor
- · Roof & lateral walls covered by laminated panels
- Separation walls made of laminated panels
- · Central platform in front of the middle door
- Internal luggage racks for passengers
- · Passenger seats Ster (LE City) / Lineo (Line)
- Manual ramp for disabled persons

ELECTRICAL EQUIPMENT

- Two batteries I2V 225 AH
- Three alternators I50 A
- Electrical box with fuses in the front left compartment
- Internal & external lights
- Fog lights with cornering function
- · Fire extinguishing system
- 24 V and 2x USB sockets on the dashboard

WINDOWS/ THERMAL COMFORT

- · Tinted simple glass with 7 opening units
- Two roof hatches, manual control
- Four heaters for the passenger compartment
- Independent heater

DRIVER'S COMPARTMENT

- Adjustable driver's seat with air suspension, headrest, 3 pts safety belt
- Front sun visor with electrical control
- Driver's separation
- Driver's box with lock
- · On board computer with fuel consumption control
- Digital tachograph
- Driver cabin with door

ADAS/GSR equipment including

- Blind spot info system (right side)
- Moving off info system
- Reverse camera
- Intelligence speed assist (speed limit display)
- Driver drowsiness attention warning
- Alcohol ignition interlock device preparation

OPTIONAL

- Ski carrier preparation
- Towing device preparation
- Other door combination available : Please see with our commercial representative
 Rear Door 800 mm (LE City)

OPTIONAL

- Electrical ramp for disabled persons
- Curtains on lateral windows
- Refrigerator integrated in the dashboard
- Cantilever seats
- Central platform 2 UFR (LE City)
 Central platform right side (LE City)
- Central platform right side (LE C
 Roof Luggage racks (LE Line)
- KOOI Luggage racks (LE LINE)

OPTIONAL

- Warning lights with open doors
- Reverse sensors
- I2 V socket on the dashboard

OPTIONAL

- Two roof hatches with electrical control
- Double glasses of the lateral, rear, driver's
- windows and passenger doorsA/C with or without heating
- Electrical defrosting of the front steps
- Electrical defrosting of the windshield

OPTIONAL

- · Driver's seat with heating system
- Driver's refrigerator (LE Line)
- Additional driver's heater
- Driver's A/C
- Movable cluster

OPTIONAL

- · Blind spot info system (Left and Right)
- Alcohol ignition interlock device

AFTER TREATMENT SYSTEM

- Hi-SCR after treatment system, main components:
- Diesel Oxydation Catalyst, Diesel Particulate Filter, Selective Catalytic Reduction of Nox with AdBlue®, Clean Up Catalyst

IVECO

Drive the road of change

ορτιοναι

Line)

ΟΡΤΙΟΝΑΙ

ορτιοναι

OPTIONAL

OPTIONAL

With spare wheel

· 320 litres diesel tank

50 litres AdBlue[®] tank (3 door version)

representative

Automatic ZE Ecolife (LE Line)

Please see with our commercial

• Lifting of the vehicle's suspensions

Reinforced shock absorbers

Automatic Voith Diwa NXT (LE City &

RIIS

Edition April 2024

GEARBOX

- LE City: Automatic ZF Ecolife
- LE Line: mechancal ZF

REAR AXLE

- Single reduction hypoid rear axle equipped with "Quiet ride gears set" for low noise
- Standard axle ratio: 5,29 (LE City) / 3,36 (LE Line)

FRONT AXLE / STEERING

- Front axle with independent wheels suspension
- Worm-type steering with integrated power steering

SUSPENSION

- Full air suspension with self- leveling sensor
- · Front: 2 combined air springs/2 shock absorbers/1 leveling sensor
- · Rear: 4 air springs/4 shock absorbers /1 stabilization bar
- Third axle 2 combined air springs/2 shock absorbers/2 leveling sensors
- Kneeling

COMPRESSED AIR

- Dual cylinder air compressor 630 cm³ (pressure 9.5 bar)
- Integrated air dryer: bleeding valves on the air tanks

BRAKES

EBS/ESP

RETARDER

· Decompression engine brake

FUEL TANK AND UREA TANK

and hand lever control

200 litres diesel tank

• 80 litres AdBlue[®] tank

TYRES AND WHEELS

· 275/70 R 22.5 tyres

The content of this technical datasheet is intended to provide information on optional equipment and is informative in nature. The content of this technical datasheet is not binding and does not represent a legally binding offer. We may extend, modify or delete the data contained in the catalogue at any time without prior notice.

- Pneumatic service and emergency braking system with two independent air circuits
- · Brake discs, front and rear, with floating calipers and ABS
- · Pneumatic parking brake, operating on the rear wheels

Hydraulic integrated retarder with brake pedal control